



UPC Code: 078477282380
Country Of Origin: China
RoHS Compliant: Yes

# IP710-DLZ

IllumaTech Dimmer Switch for 0-10V LED, Mark 7 Florescent Ballasts

IllumaTech Slide Preset Electro-Mechanical 0-10V Slide Dimmer for use with LED or Fluorescent Ballasts and Power Supplies with LED locator light, suitable for use with Class 1 or Class 2 wiring, 1200VA @ 120VAC, 1500VA @ 277VAC, 10A LED/Electronic Ballast 120/277VAC, 60Hz, 50mAmps maximum sinking current, single pole or 3-way control when used with 3-way switch - White, Ivory & Light Almond

- INNOVATIVE Designed for use with LED fixtures using 0-10V power supplies
- ADVANCED No power pack required for switching
- EXCEPTIONAL Superior quality and dimming performance
- FLEXIBLE Can be used in a single-pole or 3-way installation (with a 3-way switch, sold separately)

#### **Technical Information**

**Product Features** 

Action: Standard ON/OFF

Available Color Kits: Ivry-I Wht-W Gry-G Blk-E Brwn-B Light Almond-T, R-Red

Color: White, Ivory, Light Almond
Color Change Kit: IPKIT Series

Frequency: 60 Hz Light: LED Locator Light Load Rating: 1200VA

**Load Type :** Electronic 0-10VDC Fluorescent and 0-10VDC LED Power

Suppl

Ordering Notes: Incl White, Ivory and

Light Almond Color Kit

Preset: Preset

Protection: Radio/TV Filter

Standards and Certifications: cCSAus

Style Name: IllumaTech

Switch Type: Single-Pole & 3-Way

Type: Slide

Voltage: 120/277 VAC
Wallplate: Order Separately
Warranty: 5-Year Limited

## **Features and Benefits**

- Designed specifically for use with LED fixtures using 0-10V power supplies and Mark 7® 0-10V fluorescent ballasts
- Dual voltage 120V/277V; 50mAmps maximum sink current
- No power pack required for switching
- Provides single pole or 3-way lighting control when used with a 3-way switch
- Compatible with Decora Plus<sup>™</sup> screwless and Decora standard designer wallplates (sold separately)
- Six product options in each box with three changeable faceplates and single pole or 3-way functionality when used with a 3-way switch
- Fluid slide movement allows fine adjustment of light level with minimal effort
- Captive wraparound slide bar remains securely attached

### Patents\*

N A

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

