

## Eaton CHSPT2 surge protection device

### CHSPT2SURGE

UPC:786685971285

#### Dimensions:

- Height: 2 IN
- Length: 7.5 IN
- Width: 5 IN

Weight:.9 LB

**Notes:**5kA nominal discharge current. Has 36kA one time surge current rating.

#### Warranties:

- Limited lifetime

#### Specifications:

- **Type:** Surge protection device
- **Special Features:** Meets or exceeds the requirements specified in IBC ®2006, CBC2007, and UBC®Zone 4
- **Frequency Rating:** 60 Hz
- **Interrupt Rating:** 200 kAIC
- **Nominal Discharge Current:** 5 KA
- **Operating Voltage:** 150V L-N, 300V L-L
- **Protection:** 700V L-N, 1200V L-L, 900V N-G, 700V L-G
- **Short Circuit Rating:** 22000 KA
- **Voltage Rating:** 120/240V
- **Enclosure:** NEMA 4
- **Phase:** Single-phase
- **Surge Current:** 36 kA
- **Operating Temperature:** -40 to 50 °C

#### Supporting documents:

- [Eaton Specification Sheet - CHSPT2SURGE](#)

#### Certifications:

- UL Recognized



- cUL Certified
- UL 1449

**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.