




Color :  White

UPC Code : 078477815632

Country Of Origin : Mexico

Available Colors :



CS315-2W

15 Amp, Toggle Switch, 3-Way, Quiet Switch, Commercial Spec Grade

15 Amp, 120/277 Volt, Toggle 3-Way AC Quiet Switch, Commercial Spec Grade, Grounding, Side Wired, - White

Leviton's Commercial Specification Grade switches are designed to offer outstanding reliability and top performance in commercial settings. Ideal applications include municipal facilities, government buildings, malls, department stores, hospital and health care facilities, office buildings, schools, colleges, universities, houses of worship and cultural institutions. Leviton offers a large selection of 15 and 20 Amp Commercial switches, available in a wide variety of colors, wiring options and other features.

Technical Information

AC Horsepower Ratings

HP Rating : 1/2HP-120V 2HP-240V-277V

Electrical Specifications

Amperage : 15 A

Dielectric Voltage :
Withstands 1500V for 1 minute

Max. Amperage : 12 Amp

Temperature Rise : Maximum
30 degrees C rise

Voltage : 120/277 VAC

Environmental Specifications

Flammability : Rated V-2 per UL94

Operating Temperature : -40°
C to 65°C

Material Specifications

Actuator Material :
Thermoplastic

Base Material : PBT

Body Material : Thermoplastic

Color : White

Contacts : Silver-Cadmium .
031 Thick

Cover Material : Nylon

Strap Material : Steel

Terminal Screws : Steel 8-32

Toggle : Polycarbonate

Mechanical Specifications

Product ID : Stamped on Strap

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Product Features

Actuator Material :
Thermoplastic

Color : White

Device Type : Toggle Switch

Function : 3-Way

Termination : Side Wire

Grade : Commercial
Specification Grade

HP Rating : 1/2HP-120V 2HP-
240V-277V

Voltage : 120/277 VAC

Warranty : 10-Year Limited

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 111 : File
#152105

NEMA : WD-1 & WD-6

NOM : 057


UL Fed Spec WS896E : File
#E7458

UL Standard : UL 20

Warranty : 10-Year Limited

Wiring Diagram

Wiring Diagram
3-Way to 3-Way



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.