

BEST SELLER



## Basic PDU, 20AMP, 120 VOLT, (16)5-20R, 5-20P

P16B07M

This Panduit™ G5 Basic PDU features (16) 5-20R outlets. It is a 20 amp, 120 V, single phase PDU with a NEMA 5-20P input plug and a 10 foot (3m) power cord. The PDU is black.

### Specifications

|                              |                   |
|------------------------------|-------------------|
| Note                         | NA Only           |
| Includes                     | Mounting Hardware |
| Product Type                 | PDU               |
| Mount Orientation            | Vertical          |
| Sub Brand                    | G5                |
| Rack PDU Type                | Basic             |
| Plug Type                    | NEMA 5-20P        |
| Number of Circuit Breakers   | 0                 |
| Input Voltage (V)            | 120               |
| Input Amperage (A)           | 20                |
| Phase                        | Single Phase      |
| Frequency Compatibility (Hz) | 50/60             |
| Input Cord Length (ft.)      | 3                 |
| Input Cord Length (m)        | 10                |
| Output Receptacles           | (16)5-20R         |
| Output Voltage (V)           | 120               |
| Output Capacity (kW)         | 1.9               |
| Front Panel Display          | No                |
| Network Monitoring Port      | No                |
| SNMP Compatibility           | No                |
| Network Compatibility        | No                |
| Network Card                 | No                |
| Communications Interface     | No                |
| Daisy-Chainable / Cascadable | No                |
| LED Indicators               | No                |
| Material                     | Metal             |
| Finish/Coating               | Powder-Coated     |
| Color                        | Black             |
| Overall Height (In.)         | 32                |

## Specifications (continued)

|                                     |                                                                      |
|-------------------------------------|----------------------------------------------------------------------|
| Overall Height (mm)                 | 817                                                                  |
| Overall Width (In.)                 | 2                                                                    |
| Overall Width (mm)                  | 52                                                                   |
| Overall Depth (In.)                 | 2.1                                                                  |
| Overall Depth (mm)                  | 53                                                                   |
| Number of Rack Units                | 19                                                                   |
| Maximum Operating Temperature (°C)  | 60                                                                   |
| Maximum Operating Temperature (°F)  | 140                                                                  |
| Minimum Operating Temperature (°C)  | 10                                                                   |
| Minimum Operating Temperature (°F)  | 50                                                                   |
| Maximum Storage Temperature (°C)    | 60                                                                   |
| Maximum Storage Temperature (°F)    | 140                                                                  |
| Minimum Storage Temperature (°C)    | -20                                                                  |
| Minimum Storage Temperature (°F)    | -4                                                                   |
| Compliance Certifications           | UL 62368-1, FCC Pat 15 Class A (USA), NOM (Mexico), RETIE (Colombia) |
| Standards Met                       | UL Listed File number: E218078                                       |
| Product Warranty Period (Worldwide) | 3 Years                                                              |

## Packaging Detail

|                       |             |
|-----------------------|-------------|
| UPC                   | 61305626350 |
| Std. Pkg. Qty.        | 1           |
| Std. Pkg. Volume (cf) | 0.7639      |
| Std. Ctn. Qty.        | 0           |
| Std. Ctn. Volume (cf) | 0.0000      |